



- NOTES:**
- 1). THE MAXIMUM PUMP DISCHARGE IN THIS TYPICAL PORTABLE SEDIMENT TANK IS 125 GALLONS PER MINUTE. REPLACE THE GEOTEXTILE WHEN THE PORTABLE SEDIMENT TANK CAN NO LONGER ALLOW THIS FLOW RATE, WHEN THERE IS A TEAR, OR WHEN DIRECTED BY THE ENGINEER.
 - 2). SEVERAL UNCONNECTED OR CONNECTED IN PARALLEL PORTABLE SEDIMENT TANKS MAY BE USED WHEN A HIGHER FLOW RATE IS NEEDED TO DEWATER THE JOB.
 - 3). PLACE 72" C.M.P. SO THAT IT IS CENTERED IN THE 96" C.M.P. AND THERE IS AN EQUAL AMOUNT OF SPACE BETWEEN THE TWO PIPES.

	 ENGINEERING SUPPORT DATE 09/01/2020 RECOMMENDED	PORTABLE SEDIMENT TANK		REVIEWED DEPUTY DIRECTOR - DESIGN DATE 09/01/2020
	STANDARD NO. E-6 (2020)	SHT. 1 OF 1	APPROVED CHIEF ENGINEER DATE 09/01/2020	